



**Extremely versatile, the DECKHAND® L  
out-performs all other pipe handling methods.**

- Head unit mounts to any brand of excavator in the 40-49 metric ton class
- 360° Continuous Rotation
- Tilts up to 15°
- Shifts pipe side to side up to 8.5" in either direction
- Load locking valves holds pipe securely, regardless of hydraulic pressure
- In-cab display allows operator to safely monitor and adjust all functions, working parameters, and hydraulic settings from inside the excavator
- Requires auxiliary hydraulic circuit on excavator and dedicated case drain line
- Designed to meet ASME Below-The-Hook Lifting Standards
- Optional stick-mounted camera allows operator to see in even the most difficult spaces



### DECKHAND® L HEAD UNIT

Part Number	3000
Model Number	DHL
Excavator Wt Class	108,000 LBS / 48,987 KGS
Supply Pressure	3,200 PSI / 221 BAR
Max Flow	25 GPM / 95 LPM
Min Flow	15 GPM / 57 LPM
Main Beam Size (inches)	8x8
Capacity	40,000 LBS / 18,144 KGS
Weight	3,650 LBS / 1,658 KGS
Shipping Storage Crate	3458
Shipping Dimensions (inches)	78L X 112W X 48H
Shipping Weight w/ Stand	4,030 LBS / 1,828 KGS

# DECKHAND® COMPETITIVE ADVANTAGES

The DECKHAND® by LaValley Industries offers a long list of advantages versus traditional pipe handling methods in terms of safety, operational efficiency, and total project costs:

	<b>STRAPS &amp; CHAINS</b>	<b>VACUUM LIFTS</b>	<b>DECKHAND®</b>
<b>MAN POWER</b>	<b>2-4 PEOPLE</b>	<b>1-3 PEOPLE</b>	<b>1 PERSON</b>
Both straps/chains and vacuum lifts require extra manpower for positioning pipe.			
<b>OVERALL SAFETY</b>	<b>POOR</b>	<b>FAIR</b>	<b>EXCELLENT</b>
DECKHAND® eliminates workers in the vicinity of lifted pipe. No matter what the weather conditions, DECKHAND® offers positive grip and total control of pipe, unlike vacuum lifts.			
<b>LOAD HOLDING</b>	<b>POSITIVE</b>	<b>CAN DROP LOAD</b>	<b>POSITIVE</b>
Load hold valves on DECKHAND® arms ensure that pipe never drops, regardless of hydraulic pressure.			
<b>LOAD CONTROL</b>	<b>POOR</b>	<b>POOR</b>	<b>EXCELLENT</b>
DECKHAND® offers control of pipe in all directions. Vacuum lifts are free-swinging in one direction and cannot tilt pipe.			
<b>LOAD PLACEMENT</b>	<b>GROUND PERSONNEL REQUIRED</b>	<b>FAIR</b>	<b>EXCELLENT</b>
DECKHAND® offers powered control of pipe in all directions, which allows for fast, accurate pipe placement without any ground assistance.			
<b>PRODUCTIVITY</b>	<b>LOW</b>	<b>MODERATE</b>	<b>HIGH</b>
Straps/chains and vacuum lifts require multiple workers, while the DECKHAND® requires just one operator. Vacuum lifts are slower than DECKHAND® at moving and positioning pipe.			
<b>OFF-CENTER LIFTS</b>	<b>NO</b>	<b>NO</b>	<b>YES</b>
DECKHAND® can lift pipe off-center per operating limits.			
<b>TOTAL OWNERSHIP COST</b>	<b>MEDIUM</b>	<b>HIGH</b>	<b>LOW</b>
DECKHAND®'s robust design ensures a long lifespan and nominal maintenance costs.			
<b>LABOR COST</b>	<b>2-4 PEOPLE</b>	<b>1-3 PEOPLE</b>	<b>1 PERSON</b>
DECKHAND® also increases pipe handling production vs. other methods.			
<b>PIPE &amp; EQUIPMENT DAMAGE</b>	<b>HIGH</b>	<b>MEDIUM</b>	<b>LOW</b>
Vacuum lifts can drop pipe unintentionally or swing pipe into objects, causing pipe and/or equipment damage.			
<b>MAINTENANCE COSTS</b>	<b>LOW</b>	<b>HIGH</b>	<b>LOW</b>
DECKHAND® requires weekly greasing and occasional wear pad replacement. Vacuum lifts require suction pads to be replaced when torn or every 200 hours, and filters to be replaced daily in certain weather conditions (diesel engine also requires daily fueling and maintenance).			
<b>INSURANCE COSTS</b>	<b>HIGH</b>	<b>MEDIUM</b>	<b>LOW</b>
With DECKHAND®, fewer ground workers equals lower insurance costs.			