

The Toughest Most Versatile Mud Pumps Ever Designed for the HDD Industry

PURPOSE BUILT

Designed and developed specifically for use with drilling mud.

TOUGH

Liquid-cooled and designed to remain submerged. Built to handle particles up to 5 inches in diameter with up to 8-inch discharge. High chrome alloy steel components with extended run dry capability.

ADVANCED

Active health monitoring of critical components prevents unplanned downtime.



PPL





LAVALLEYINDUSTRIES.COM





SMART FEATURES AND KEY BENEFITS

Advanced internal liquid-cooling system and high chrome alloy steel pump components (650+ Brinell) ensure industry leading service life.

Specialized inlet and impeller design are built to handle particles up to 5 inches in diameter which reduces frequency of cleaning.

Reversible impeller direction allows operator to clear lodged particles, all from the control panel.

Active health monitoring of critical components automatically notifies operator of needed maintenance, preventing unplanned downtime and keeping productivity high.

Variable pump speed enables pump flow to be optimized based on flow requirements for maximum efficiency.

Critical data including power level, cycle logging, pump temperature, coolant temperature, pump motor RPM and fuel level are monitored and clearly displayed for operator.

SMARTER, TOUGHER, BETTER



TECHNICAL SPECIFICATIONS

PARTICLE SIZE 5 IN / 127 MM

MAX FLOW RATE 14LB 120 VIS SLURRY

1400 GPM 5300 LPM

PUMP SPEED 500-800 RPM NORMAL OP. SPEED 625 RPM

> DISCHARGE 6-8 IN / 152 MM

COOLANT PROPYLENE GLYCOL/WATER

> WEIGHT 3750 LB / 1700 KG

> > LENGTH 83 IN / 211 CM

WIDTH 34 IN / 86 CM

HEIGHT 59 IN / 150 CM

LaValley Industries LAVALLEYINDUSTRIES.COM