



S

TONGHAND®

TORQUE UP!

Exit Side Solution for the
Horizontal Drilling Industry

REVOLUTIONARY

Grip it, spin it and torque it up – all from the
safety and comfort of the excavator cab.

PRECISE

In-cab display and control system allow you to torque
pipe joints precisely at the touch of a button.

VERSATILE

Patented Gull Wing design and Roller Arms allow for
ease of use with reamers, subs and rotating pipe strings.



LaValley Industries.

Learn more at
LAVALLEYINDUSTRIES.COM



TONGHAND®

MAKING AND BREAKING JUST GOT A WHOLE LOT EASIER

FEATURES

Patented TongVise™ easily makes and breaks joints with up to 70,000 lb-ft of torque.

Works with reamers, adapter sub connections, and drill pipe connections ranging from 4.13" to 6.75" OD.

Patented roller arms and shift function allow you to thread and unthread all connections.

Gull wing design allows you to easily move arms out of way to make and break reamers.

Versatile design allows TONGHAND®S to work as a pipe handler for precise placement of drill rod on rigs, racks, or trucks.

BENEFITS

Safely and efficiently make, break, and move pipe. No need for back-breaking wrenches or having crew in danger zones.

Single operator can perform all functions from the safety and comfort of the excavator cab.

TONGHAND®S control system and in-cab monitor allows you to torque pipe joints to your specified torque value.



TONGHAND®S EXIT SIDE WRENCH



TECHNICAL SPECIFICATIONS

MAKE/BREAK TORQUE

70,000 LB-FT

LIFTING CAPACITY

5,000 LBS


2,267 KGS

PIPE DIAMETER (OD)

MIN 4.13"

MAX 6.75"

CAN HANDLE UP TO 8" PIPE JOINTS
WITH REDUCED TORQUE ABILITY



LAVALLEYINDUSTRIES.COM